

P/N	Size/Cdr	Insul	Description	Temp Rating
P81J20-2-507BN	20 Solid	FEP	Type J, SLE, 20AWG Solid, FEP/FEP Brown	200C/392F
P81J20-4-507	20 7/28	FEP	Type J, SLE, 20AWG Stranded FEP/FEP Brown	200C/392F
P81J24-2-507BN	24 Solid	FEP	Type J, SLE, 24AWG Solid, FEP/FEP Brown	200C/392F
P81J24-4-507	24 7/32	FEP	Type J, SLE, 24AWG, Stranded FEP/FEP Brown	200C/392F
P81J30-2-506BN	30 Solid	FEP	Type J, SLE, 30AWG Solid, FEP/FEP Brown	200C/392F
P81J36-2-506BN	36 Solid	FEP	Type J, SLE, 36AWG Solid, FEP/FEP Brown	200C/392F
P81J20-2-304	20 Solid	E GB	Type J, SLE, 20AWG, Solid, Glass Braid/Glass Braid	482C/900F
P81J20-4-304	20 7/28	E GB	Type J, SLE, 20AWG, Stranded, Glass Braid/Glass Braid	482C/900F
P81J24-2-304	24 Solid	E GB	Type J, SLE, 24AWG, Solid, Glass Braid/Glass Braid	482C/900F
P81J30-2-305	30 Solid	E GB	Type J, SLE, 30AWG, Solid, Glass Serve/Glass Braid	482C/900F
P81J36-2-305	36 Solid	E GB	Type J, SLE, 36AWG, Solid, Glass Serve/Glass Braid	482C/900F
P81J20-2-516	20 Solid	PFA	Type J, SLE, 20AWG, Solid, PFA/PFA Brown	260C/500F
P81J24-2-516	24 Solid	PFA	Type J, SLE, 24AWG, Solid, PFA/PFA Brown	260C/500F
P81J30-2-516CL	30 Solid	PFA	Type J, SLE, 30AWG, Solid, PFA/PFA Clear	260C/500F
P81J36-2-516CL	36 Solid	PFA	Type J, SLE, 36AWG, Solid, PFA/PFA Clear	260C/500F
P81J40-2-516CL	40 Solid	PFA	Type J, SLE, 40AWG, Solid, PFA/PFA Clear	260C/500F
P/N	Size/Cdr	Insul	Description	Temp Rating
P82K20-2-507	20 Solid	FEP	Type K, SLE, 20AWG, Solid, FEP/FEP Brown	200C/392F
P82K20-4-507	20 7/28	FEP	Type K, SLE, 20AWG, Stranded, FEP/FEP Brown	200C/392F
P82K24-2-507	24 Solid	FEP	Type K, SLE, 24AWG, Solid, FEP/FEP Brown	200C/392F
P82K30-2-506BN	30 Solid	FEP	Type K, SLE, 30AWG, Solid, FEP/FEP Brown	200C/392F
P82K36-2-506BN	36 Solid	FEP	Type K, SLE, 36AWG, Solid, FEP/FEP Brown	200C/392F
P82K20-2-304	20 Solid	E GB	Type K, SLE, 20AWG, Solid, Glass Braid/Glass Braid	482C/900F
P82K20-4-304	20 7/28	E GB	Type K, SLE, 20AWG, Stranded, Glass Braid/Glass Braid	482C/900F
P82K24-2-304	24 Solid	E GB	Type K, SLE, 24AWG, Solid, Glass Braid/Glass Braid	482C/900F
P82K30-2-305	30 Solid	E GB	Type K, SLE, 30AWG, Solid, Glass Serve/Glass Braid	482C/900F
P82K36-2-305	36 Solid	E GB	Type K, SLE, 36AWG, Solid, Glass Serve/Glass Braid	482C/900F
P82K40-2-305	40 Solid	E GB	Type K, SLE, 40AWG, Solid, Glass Serve/Glass Braid	482C/900F
P82K20-2-516	20 Solid	PFA	Type K, SLE, 20AWG, Solid, PFA/PFA Brown	260C/500F
P82K20-4-516	20 7/28	PFA	Type K, SLE, 20AWG, Stranded PFA/PFA Brown	260C/500F
P82K24-2-516	24 Solid	PFA	Type K, SLE, 24AWG, Solid, PFA/PFA Brown	260C/500F
P82K30-2-516CL	30 Solid	PFA	Type K, SLE, 30AWG, Solid, PFA/PFA Clear	260C/500F
P82K36-2-516BN	36 Solid	PFA	Type K, SLE, 36AWG, Solid, PFA/PFA Brown	260C/500F
P82K36-2-516CL	36 Solid	PFA	Type K, SLE, 36AWG, Solid, PFA/PFA Clear	260C/500F
P82K40-2-516CL	40 Solid	PFA	Type K, SLE, 40AWG, Solid, PFA/PFA Clear	260C/500F
P82K20-2-321	20 Solid	S GB	Type K, SLE, 20AWG, Solid, Glass Braid/Glass Braid	704C/1300F
P82K20-2-301	20 Solid	VS	Type K, SLE, 20AWG, Solid, Vitreous Silica/Vitreous Silica Heavy Build	871C/1600F
P82K20-2-365	20 Solid	VS	Type K, SLE, 20AWG, Solid, Vitreous Silica/Vitreous Silica	871C/1600F
P82K20-2-350	20 Solid	Ceramic	Type K, SLE, 20AWG, Solid, CeramicFiber /Ceramic Fiber Heavy Build	1204C/2200F
P82K20-2-355	20 Solid	Ceramic	Type K, SLE, 20AWG, Solid, Ceramic Fiber/Ceramic Fiber	1204C/2200F
P/N	Size/Cdr	Insul	Description	Temp Rating
P83T20-2-507	20 Solid	FEP	Type T, SLE, 20AWG, Solid, FEP/FEP Brown	200C/392F
P83T20-4-507	20 7/28	FEP	Type T, SLE, 20AWG, Stranded, FEP/FEP Brown	200C/392F
P83T24-2-507	24 Solid	FEP	Type T, SLE, 24AWG, Solid, FEP/FEP Brown	200C/392F
P83T24-4-507	24 7/32	FEP	Type T, SLE, 24AWG, Stranded, FEP/FEP Brown	200C/392F
P83T30-2-506BN	30 Solid	FEP	Type T, SLE, 30AWG, Solid, FEP/FEP Brown	200C/392F
P83T36-2-506BN	36 Solid	FEP	Type T, SLE, 36AWG, Solid, FEP/FEP Brown	200C/392F
P83T40-2-506BN	40 Solid	FEP	Type T, SLE, 40AWG, Solid, FEP/FEP Brown	200C/392F
P83T36-2-305	36 Solid	E GB	Type T, SLE, 36AWG, Solid, Glass Serve/Glass Braid	482C/900F
P83T24-2-516	24 Solid	PFA	Type T, SLE, 24AWG, Solid, PFA/PFA Brown	260C/500F
P83T24-4-516	24 7/32	PFA	Type T, SLE, 24AWG, Stranded, PFA/PFA Brown	260C/500F
P83T30-2-516CL	30 Solid	PFA	Type T, SLE, 30AWG, Solid, PFA/PFA Clear	260C/500F
P83T30-2-516BN	30 Solid	PFA	Type T, SLE, 30AWG, Solid, PFA/PFA Brown	260C/500F
P83T36-2-516CL	36 Solid	PFA	Type T, SLE, 36AWG, Solid, PFA/PFA Clear	260C/500F
P83T40-2-516CL	40 Solid	PFA	Type T, SLE, 40AWG, Solid, PFA/PFA Clear	260C/500F